

Twilight switch

VEPAL

Twilight switch built for pole installation.
Vepal moreover can be wall mounted, thanks to the bracket supplied.



- 1 Cover: shockproof polycarbonate resin
- 2 Wall fastening bracket

WALL / POLE-MOUNTING TWILIGHT SWITCHES

- Connectable load:
 - Incandescent lamps: 800 W / 230 V ($\cos\varphi \geq 0.8$)
 - Fluorescent lamps: 360 W / 230 V ($\cos\varphi \geq 0.8$)
- Output: relay with NO contact
- Relay capacity: 10A / 250V AC on resistive load
- Sensitivity: 3 ÷ 70 lux
- Hysteresis: 1 ÷ 10 lux
- Delay: 10 s fixed




GENERAL CHARACTERISTICS


Power supply	V AC	230 (-20% ÷ +10%) - 50 / 60 Hz
Absorption	VA (W)	8 (1)
Fastened		Wall / Pole
Contacts capacity 250 V AC	A	10 (resistive load)
Sensitivity	lux	3 ÷ 70
Intervention time	s	10
Hysteresis factor	lux	1 ÷ 10
Operating temperature	°C	0 ÷ +50
Storage temperature	°C	-10 ÷ +60
Relative humidity	RH	20% ÷ 90% non condensing

DIMENSIONS (mm)


Front view



Side view



CONNECTION DIAGRAM



- 1 Sensitivity regulation
- 2 Hysteresis regulation

Code	Model	Fastened	Sensitivity
VJ57370000	Vepal	Wall / Pole	3 ÷ 70 lux

REFERENCE STANDARDS

Compliance with Community Directives: 2014/35/EU (LVD) and 2014/30/EU (EMCD)
is declared with reference to the following standards: • Safety and E.M. Compatibility: 60669-2-1