ESYLUX•

DATA SHEET

AFL SUN LED 50W 3K black

Order description AFL SUN LED 50W 3K BK Item number EL10810237

4015120810237

GTIN



IP 65 230 V~ 160° (CRI 80)

Energy Conservation Solutions 'our promise, you'll save'

Product description

- LED floodlight with high-grade die-cast aluminium housing and integrated motion detector with 160° field of detection for convenient lighting control
- 50 W LED luminous efficiency corresponds to 215 W light bulb, light colour approx. 3000 K white
- High light yield of 80 lm/W, excellent colour rendering index Ra 80

Technical data

GENERAL	
Conformity	CE, RoHS, WEEE
warranty	3-year
MOUNTING	
Installation type	Surface mounting
Mounting location	Wall
HOUSING	
Dimensions	Length 290 mm x Width 227 mm x Height/ Depth 86 mm
Weight	1980 g
Material	Aluminium and UV-stabilised plastic
Protection type	IP 65
Permissible ambient temperature	-25 °C+40 °C
Colour	Black, similar to RAL 9005
Terminal	2,5 mm² / 1,5 mm²
ELECTRICAL VERSION	
Protection class	I
Nominal voltage	230 - 230 V / 50 Hz
Stand-by consumption	0.5 W

LIGHT	
Diffusor	transparent
Light emission	direkt
Beam angle	110 °
Flicker factor	<20 %
Rated output	45 W
Luminous Flux (light)	5400 lm
Luminous efficacy	120 lm/W
LED service life	L80B50 = 50.000 h
Colour temperature	3000 K
Colour rendering index Ra	> 80
Energy efficiency class	A++ to A
SENSORS	
Detection angle	160°
Detection range diagonally	12 m
Field of detection	50 m ²
Range adjustment	mechanically with included cut to size lens mask

	mask
Recommended installation height	2,5 m
Max. mounting height	4 m
Number of parallel switchable detectors	10

ESYLUX•

DATA SHEET


AFL SUN LED 50W 3K black

Order description	Item number	GTIN
AFL SUN LED 50W 3K BK	EL10810237	4015120810237


Accessories

Product designation	Item number	GTIN
Wall Arm 700 BK	EL10810534	4015120810534
Ground Spike BK	EL10810558	4015120810558

Scale drawing



Field of detection




Energy Conservation Solutions 'our promise, you'll save'

Head-on to detector

Passage area / diagonally to detector

Light distribution



Energy Conservation Solutions Pty Ltd

Exclusive Distributor for ESYLUX in Australia Locations: VIC/TAS, NSW, QLD, ACT, SA/NT & WA Phone: 1300 306 136 For contact details visit: www.ecs.net.au

2/2