

## DATA SHEET

### Order description

IDLELS05005830WH001-1000

### Item number

E010300103

### GTIN

4015120300103

110 V - 230 V ~	IP 40	CQS 80 - 85	CRI 80	LED 3000 K
--------------------	-------	----------------	-----------	---------------



### Product description

- LED downlight, 3000K with opal cover (diffuser), 5W, for ceiling mounting without additional accessories
- High light quality and system performance
- Operating device 1-10V, included

### Technical data

#### GENERAL

Conformity	CE, RoHS, WEEE
warranty	5-year

#### MOUNTING

Installation type	Recessed mounting
Mounting location	Ceiling
Installation dimension	Installation depth 45 mm, Ø 68 mm

#### HOUSING

Dimensions	Height/Depth 45 mm, Ø 97 mm
Weight	230 g
Material	powder-coated aluminium
Protection type	IP 40 / IP 44 below the ceiling (built-in)
Permissible ambient temperature	-20 °C...+40 °C
Colour	white, similar to RAL 9003
Glow wire test in accordance with IEC 60695-2-10	650 °C - 30 s

#### ELECTRICAL VERSION

Protection class	II
Nominal voltage	110 - 240 V / 50 - 60 Hz

#### LIGHT

Diffusor	opal
Light emission	direkt
Beam angle	100 °
Unified Glare Rating	≤ 25
Flicker factor	<3 %
Rated output	5 W
Luminous Flux (light)	380 lm
Luminous efficacy	76 lm/W
LED service life	L80B50 = 35.000 h
Colour temperature	3000 K
Colour rendering index Ra	> 80
Color Quality Scale	> 80
Energy efficiency class	A++ to A

### Accessories

Product designation	Item number	GTIN
Indoor downlight ring 65	E010300288	4015120300288
Indoor downlight cable, 1 m	E010300295	4015120300295

## DATA SHEET

### Order description

IDLELS05005830WH001-1000


### Item number

E010300103


### GTIN

4015120300103


### Scale drawing



### Light distribution



### Circuit diagram



Standard operation

**Energy Conservation Solutions Pty Ltd**

Exclusive Distributor for ESYLUX in Australia Locations:

VIC/TAS, NSW, QLD, ACT, SA/NT & WA

Phone: **1300 306 136**

For contact details visit: [www.ecs.net.au](http://www.ecs.net.au)