

DATA SHEET

Order description

IDLELS05005830WH00DALI00

Item number

E010300202

GTIN

4015120300202

110 V - 230 V ~	IP 40	CQS 80 - 85	CRI 80	LED 3000 K
--------------------	-------	----------------	-----------	---------------



Product description

- LED downlight, 3000K with opal cover (diffuser), 5W, for ceiling mounting without additional accessories
- High light quality and system performance
- Operating device DALI, included

Technical data

GENERAL	
Conformity	CE, RoHS, WEEE
warranty	5-year
MOUNTING	
Installation type	Recessed mounting
Mounting location	Ceiling
Installation dimension	Installation depth 45 mm, Ø 68 mm
HOUSING	
Dimensions	Height/Depth 45 mm, Ø 97 mm
Weight	108 g
Material	powder-coated aluminium
Protection type	IP 40 / IP 44 below the ceiling (built-in)
Permissible ambient temperature	-20 °C...+40 °C
Colour	white, similar to RAL 9003
Glow wire test in accordance with IEC 60695-2-10	650 °C - 30 s

ELECTRICAL VERSION	
Protection class	II
Nominal voltage	110 - 240 V / 50 - 60 Hz
LIGHT	
Diffusor	opal
Light emission	direkt
Beam angle	100 °
Unified Glare Rating	≤ 25
Flicker factor	<3 %
Rated output	5 W
Luminous Flux (light)	380 lm
Luminous efficacy	76 lm/W
LED service life	L80B50 = 35.000 h
Colour temperature	3000 K
Colour rendering index Ra	> 80
Color Quality Scale	> 80
Energy efficiency class	A++ to A


Accessories

Product designation	Item number	GTIN
Indoor downlight ring 65	E010300288	4015120300288
Indoor downlight cable, 1 m	E010300295	4015120300295


DATA SHEET

Order description	Item number	GTIN
IDLELS05005830WH00DALI00	E010300202	4015120300202


Scale drawing



Light distribution



Circuit diagram



Standard operation

Energy Conservation Solutions Pty Ltd
Exclusive Distributor for ESYLUX in Australia Locations:
VIC/TAS, NSW, QLD, ACT, SA/NT & WA
Phone: 1300 306 136
For contact details visit: www.ecs.net.au