

DATA SHEET

Order description	Item number	GTIN
IDLELS07020840WH00DALI00	E010300257	4015120300257

110 V - 230 V ~	IP 40	CQS 80 - 85	CRI 80	LED 4000 K
--------------------	-------	----------------	-----------	---------------



Product description

- LED downlight, 4000K with opal cover (diffuser), 18W, for ceiling mounting without additional accessories
- High light quality and system performance
- Operating device DALI, included

Technical data

GENERAL	
Conformity	CE, RoHS, SundaHus, WEEE
warranty	5-year
MOUNTING	
Installation type	Recessed mounting
Mounting location	Ceiling
Installation dimension	Installation depth 27 mm, Ø 225 mm
HOUSING	
Dimensions	Height/Depth 27 mm, Ø 240 mm
Weight	696 g
Material	powder-coated aluminium
Protection type	IP 40 / IP 44 below the ceiling (built-in)
Permissible ambient temperature	-20 °C...+40 °C
Colour	white, similar to RAL 9003
Glow wire test in accordance with IEC 60695-2-10	650 °C - 30 s

ELECTRICAL VERSION

Protection class	II
Nominal voltage	110 - 240 V / 50 - 60 Hz

LIGHT

Diffusor	opal
Light emission	direkt
Beam angle	120 °
Unified Glare Rating	≤ 25
Flicker factor	<3 %
Rated output	18 W
Luminous Flux (light)	1600 lm
Luminous efficacy	88 lm/W
LED service life	L80B50 = 35.000 h
Colour temperature	4000 K
Colour rendering index Ra	> 80
Color Quality Scale	> 80
Energy efficiency class	A++ to A


Accessories

Product designation	Item number	GTIN
Indoor downlight ring 225	E010300264	4015120300264
ELSA 225 Surface Mounting Frame WHITE	E010300899	4015120300899
Indoor downlight cable, 1 m	E010300295	4015120300295


DATA SHEET

Order description	Item number	GTIN
IDLELS07020840WH00DALI00	E010300257	4015120300257


Scale drawing



Light distribution



Circuit diagram



Standard operation

Energy Conservation Solutions Pty Ltd
Exclusive Distributor for ESYLUX in Australia Locations:
VIC/TAS, NSW, QLD, ACT, SA/NT & WA
Phone: **1300 306 136**
For contact details visit: www.ecs.net.au