

DATA SHEET

Order description


PD-C 360i/8 ELC

Item number

EP10427602

GTIN

4015120427602



Product description

- Presence detector with 360° field of detection for ceiling mounting
- Range of up to 8 m in diameter at a recommended installation height of 3 m (maximum mounting height 5 m)
- Automatic light control to a constant brightness level depending on presence and natural light (ESYLUX Light Control interface)
- Default factory settings ensure immediate operability

Technical data

GENERAL	
Conformity	CE, RoHS, SundaHus, WEEE
warranty	5-year
MOUNTING	
Installation type	Recessed mounting
Mounting location	Ceiling
Installation dimension	Installation depth 24 mm, Ø 60 mm
HOUSING	
Dimensions	Height/Depth 38 mm, Ø 108 mm
Weight	255 g
Material	UV-stabilised polycarbonate
Protection type	recessed-mounted IP 20, IP 54 with surface-mounted box (order separately), IP 20 as recessed ceiling-mounted version (order installation set separately)
Permissible ambient temperature	-25 °C...+50 °C
Relative humidity	5 - 93 %, non-condensing
Colour	white, similar to RAL 9010
Terminal	2,5 mm ² / 1,5 mm ²
ELECTRICAL VERSION	
Protection class	III
Nominal voltage	9 - 22 V
SENSORS	
Power consumption	0,3 W
Detection angle	360°

Detection range diagonally	8 m
Detection range head-on	6 m
Detection range zone de présence	4 m
Field of detection	50 m ²
Recommended installation height	3 m
Max. mounting height	5 m
Light measurement	mixed light
Level of brightness	5 - 2000 lx
Number of light channels	4
Number of switching contacts	2
Slave input	No
Fully automatic	yes
Semi-automatic	yes
Impulse feature	yes
Constant lighting control	true
Switching delay from "dark to light" [s]	300 s
Switching delay from "light to dark" [s]	30 s

CONTROL

Channel 1	ESYLUX light control
Interface	Switching/Dimming
Contact	Bus system
Switch-off delay channel 1	60 s - 240 min
Orientation light	10 % to 50 % luminous efficiency
Switch-off delay time, orientation light	approx. 1 min.-240 min.
Orientation light	10 % to 50 % luminous efficiency
Switch-off delay time, orientation light	approx. 1 min.-240 min.
Master/slave function	true

DATA SHEET


Order description	Item number	GTIN
PD-C 360i/8 ELC	EP10427602	4015120427602

Constant lighting control	true	Manual override	yes, via IR
---------------------------	------	-----------------	-------------


Accessories

Product designation	Item number	GTIN
ESY-Pen	EP10425356	4015120425356
Mobil-PDi/MDi-universal	EP10433993	4015120433993
Surface-mounted box-C IP 20	EP10425370	4015120425370
Surface-mounted box C IP 54	EP10425905	4015120425905
Cover set-C360/8	EP10425936	4015120425936
Ceiling-mounted set-C	EP10425929	4015120425929
Basket guard 165/70	EM10425615	4015120425615
Basket guard 180/90	EM10425608	4015120425608
Mobil-PDi/MDi	EM10425509	4015120425509

Scale drawing



Field of detection



- Operating area approx. Ø 4 m
- Head-on to detector approx. Ø 6 m
- Passage area / diagonally to detector approx. Ø 8 m

Energy Conservation Solutions Pty Ltd
Exclusive Distributor for ESYLUX in Australia Locations:
VIC/TAS, NSW, QLD, ACT, SA/NT & WA
Phone: **1300 306 136**
For contact details visit: **www.ecs.net.au**