

DATA SHEET

Order description

PNLCEL14030840WH00ELCS000

Item number

EQ10126093

GTIN

4015120126093



Product description

- LED light with opal (MILKY) cover (diffuser)
- Can be used as a panel light for ceiling systems with concealed or visible mounting rails for system dimensions 1200 x 300 mm (please note any special features and restrictions of the ceiling system manufacturer)
- LED output 30 W
- Light for ESYLUX Light Control for interlinking with ESYLUX Light Controller via RJ45 (not included)
- Colour temperature approx. 4000 K (neutral white)

Technical data

GENERAL	
Conformity	CE, RoHS, WEEE
warranty	5-year
MOUNTING	
Installation type	Recessed mounting
Mounting location	Ceiling
Installation dimension	Installation length 1200 mm x Installation width 300 mm x Installation depth 140 mm
HOUSING	
Dimensions	Length 1195 mm x Width 296 mm x Height/Depth 91 mm
Weight	4400 g
Material	Varnished steel
Surface finish	frosted
Protection type	IP 20
Permissible ambient temperature	0 °C...+40 °C
Relative humidity	5 - 93 %, non-condensing
Colour	white, similar to RAL 9003
Terminal	RJ45
Glow wire test in accordance with IEC 60695-2-10	650 °C - 30 s

ELECTRICAL VERSION

Protection class	III
Nominal voltage	42 - 42 V

LIGHT

Diffuser	linear-prismatic / semi-opal
Light emission	direkt
Beam angle	90 °
Unified Glare Rating	≤ 19
Flicker factor	0%
Rated output	32 W
Luminous Flux (light)	3420 lm
Luminous efficacy	106 lm/W
LED service life	L70B50 = 100.000 h, L80B50 = 65.000 h, L90B50 = 30.000 h, L80B10 = 50.000 h
Colour temperature	4000 K
Colour rendering index Ra	> 80
Colour tolerance	SDCM <3
Color Quality Scale	> 80
Photobiological safety	Risk group 0
Energy efficiency class	A++ to A


DATA SHEET

Order description	Item number	GTIN
PNLCEL14030840WH00ELCS000	EQ10126093	4015120126093


Accessories

Product designation	Item number	GTIN
PNL drop protection	EQ10121616	4015120121616

Scale drawing



Light distribution



Energy Conservation Solutions Pty Ltd

Exclusive Distributor for ESYLUX in Australia Locations:

VIC/TAS, NSW, QLD, ACT, SA/NT & WA

Phone: **1300 306 136**

For contact details visit: www.ecs.net.au