

DATA SHEET

Order description

PDLPRA04060840STPODIM0000

Item number

EV10125331

GTIN

4015120125331



Product description

- LED design pendant light with prismatic (CRYSTAL) cover (diffuser)
- High-quality pendant light, designed by the design agency, Peter Schmidt
- LED output 60W
- Integrated ballast (for dimming by double button), installation without further accessories
- 2 LED light panels (up and downlight) for direct and indirect lighting
- Colour temperature: approx. 4000 K (neutral white)

Technical data

GENERAL	
Conformity	CE, RoHS, WEEE
warranty	5-year
MOUNTING	
Installation type	Pendant
Mounting location	Ceiling
HOUSING	
Dimensions	Length 1200 mm x Width 335 mm x Height/Depth 28 mm
Weight	9000 g
Material	Aluminium
Protection type	IP 20
Permissible ambient temperature	0 °C...+40 °C
Colour	Chrome
Terminal	2,5 mm ² / 1,5 mm ²
Glow wire test in accordance with IEC 60695-2-10	650 °C - 30 s

ELECTRICAL VERSION

Protection class	II
Nominal voltage	230 - 230 V / 50 - 60 Hz


LIGHT

Diffusor	micro-prismatic / transparent
Light emission	direkt/indirekt
Beam angle	98 °
Unified Glare Rating	≤ 16
Flicker factor	<3 %
Rated output	60 W
Luminous Flux (light)	6300 lm
Luminous efficacy	105 lm/W
LED service life	L80B10 = 50.000 h
Colour temperature	4000 K
Colour rendering index Ra	> 80
Colour tolerance	SDCM <3
Color Quality Scale	CQS > 80
Photobiological safety	Risk group 0
Energy efficiency class	A++ to A


DATA SHEET

Order description	Item number	GTIN
PDLPRA04060840STPODIM0000	EV10125331	4015120125331

Scale drawing



Light distribution



Energy Conservation Solutions Pty Ltd

Exclusive Distributor for **ESYLUX** in Australia Locations:

VIC/TAS, NSW, QLD, ACT, SA/NT & WA

Phone: **1300 306 136**

For contact details visit: www.ecs.net.au