



DA'SEL[®] LED Panel

DA'SEL quality LED panel luminaires provide a soft, bright luminance that is gentle on the eyes and ideal for both domestic and commercial environments. Thanks to use of an edge-lighting design, the output is uniform across the panel without any dark or weak spots, and the super-low profile will provide a nice clean ceiling line.

The DA'SEL LED panel features a white powdercoated aluminium frame with a smooth profile to blend seamlessly into a standard T-bar structure, and is available in 600 mm x 300 mm, 600 mm square and 1200 mm x 300 mm formats.

LED PANEL LIGHT



FEATURES

- » 50,000 hr LEDs
- » Short circuit protection
- » Innovative Plug-and-Play connector
- » Flat head screws on rear
- » Ultra-low profile 11 mm



APPLICATIONS

- » Showrooms
- » Offices, boardrooms
- » Hospitals
- » Hotels / motels
- » Retail outlets

OPTIONS

- » Standard or DALI dimming
- » Surface mount frame
- » Plaster frame
- » Emergency add-on
- » Motion sensor


SPECIFICATIONS

Model	DTP2224	DTP2324	DTP4324	
Dimensions	600mm x 300mm	600 mm x 600 mm	1200mm x 300mm	
Supply Voltage	200-240 VAC 50 / 60 Hz			
Power (nom.)	22 W	32 W	32 W	for optional colour temperature change 4K to: 5K = 5000 K
CCT	4000 K			
Luminous Flux	1760 lm ± 5%	2950 lm ± 5%	3080 lm ± 5%	
Efficacy	80 lm / W	92 lm / W	96 lm / W	for dimming option add: D = regular DD = DALI
Power Factor	≥ 0.9			
CRI	≥ 80			
Ta	50° C			
IP / IK Rating	IP20 / IK07			



LED PANEL LIGHT




LIGHTING DATA



DTP4304

Utilisation Table (TM5)						FPB430W4K.IES					
Reflectances			Room Index								
C	W	F	0.75	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0
70	50	20	58	66	73	78	85	90	93	98	100
70	30	20	51	59	66	72	79	85	89	94	97
70	10	20	45	53	61	67	75	80	84	90	94
50	50	20	56	64	71	76	82	87	90	94	96
50	30	20	50	58	65	70	77	82	86	90	94
50	10	20	45	53	60	65	73	78	82	88	91
30	50	20	55	62	69	73	80	84	86	90	93
30	30	20	49	57	64	69	75	80	83	88	90
30	10	20	45	52	59	64	72	77	80	85	88
0	0	0	43	50	57	62	68	73	76	81	84
BZ-class			4	4	4	4	4	4	4	4	4
			SHRnom : 1.50			SHRmax : 1.609					


DIMENSIONS



MOUNTING OPTIONS

- DTPSM23** Surface frame 602mm x 302mm
- DTPSM66** Surface frame 602mm x 602mm
- DTPSM123** Surface frame 1202mm x 302mm
(all frames are 52mm deep)

- DTPPF63** Plaster frame 600mm x 300mm
- DTPPF66** Plaster frame 600mm x 600mm
- DTPPF123** Plaster frame 1200mm x 300mm



Characteristics and specifications may change without notice. All electrical installations / connections should be carried out by a competent person at all times. Application images are indicative only and may not contain actual ECS product. The information contained in this publication is typical and must not be interpreted as a guarantee of individual product performance.