

DATA SHEET

ELC SmartDriver x4 BT

Order description


CU-ELC Box DALI BT

Item number

EC10430688

GTIN

4015120430688



Product description

- Light control for up to four ELC lights (ELC = ESYLUX Light Control)
- Integrated constant lighting control for optimum energy efficiency
- Two push button inputs for conventional buttons (230 V)
- Compatible with selected DALI buttons and DALI I/O devices
- Manual override and scenes in four separate light channels
- Lights are connected via RJ45
- Can be connected to additional ELC light controls via DALI
- Integrated Bluetooth module for easy operation using a smartphone app (Android, iOS)

Technical data

GENERAL	
Special product features	ESYLUX Light Control
Conformity	CE, RoHS, WEEE
warranty	5-year
MOUNTING	
Installation type	Recessed mounting
Mounting location	Ceiling
HOUSING	
Dimensions	Length 474 mm x Width 264 mm x Height/Depth 75 mm
Weight	3000 g
Material	Steel, galvanised
Protection type	IP 20
Permissible ambient temperature	0 °C...+40 °C
Relative humidity	5 - 93 %, non-condensing
Colour	white

Terminal	2,5 mm ² / 1,5 mm ²
----------	---

ELECTRICAL VERSION

Protection class	I
Nominal voltage	230 - 230 V / 50 - 60 Hz
Stand-by consumption	7.5 W

CONTROL

Number of light channels	4
Number of light groups	10
Number of inputs	2
Number of switching contacts	2
Number of scenes	4
Orientation light	disabled/10 - 50 %, 2 values can be selected
Constant lighting control	true
Daytime depending orientation light	true
HCL-lighting control	false
Number of outputs luminaires ELC	4
Number of outputs luminaires DALI	4

DATA SHEET

ELC SmartDriver x4 BT

Order description	Item number	GTIN
CU-ELC Box DALI BT	EC10430688	4015120430688

Accessories

Product designation	Item number	GTIN
Connection cable RJ45 5 m white	EC10430695	4015120430695
Connection cable RJ45 10 m white	EC10430749	4015120430749
Cable set RJ45, 5 m, 4 lights	EC10431142	4015120431142
Cable set RJ45, 10 m, 4 lights	EC10431159	4015120431159

Scale drawing

