

DATA SHEET

AFL BASIC LED 50 W 4 K WH

Order description


AFL BASIC LED 50W 4000K

Item number

EL10810763

GTIN

4015120810763



Product description

- LED floodlight with compact aluminium housing for unobtrusive installation, white
- 50 W light output with 4000 K light colour (neutral white)
- Excellent efficiency of approx. 100 lm/W

Technical data

GENERAL	
Conformity	CE, RoHS, WEEE
warranty	3-year
MOUNTING	
Installation type	Surface mounting
Installation position	Wall
HOUSING	
Dimensions	length 252 mm x width 240 mm x Height/Depth 60 mm
Weight	1,27 kg
Housing material	Aluminium and UV-stabilised plastic
Protection type	IP 65
Permissible ambient temperature	-25 °C...+40 °C
Colour	white
Terminal	1.5 mm ²
Glow wire test in accordance with IEC 60695-2-10	650 °C - 30 s
ELECTRICAL VERSION	
Protection class	I
Nominal voltage	220 - 240 V / 50 - 60 Hz
LIGHT	

Diffusor	transparent
Light emission	Direct
Beam angle	120 °
Unified Glare Rating	<30
Flicker factor	<30%
Rated output	50,0 W
Luminous Flux (light)	5000 lm
Luminous efficacy	100 lm/W
LED service life	L80B50 = 50.000 h
Colour temperature	4000 K
Colour rendering index Ra	>80
Color Quality Scale	>80
Photobiological safety	Risk group 0
Energy efficiency class	A++ to A

SENSORS

Detection angle	120° horizontally and vertically rotatable +/- 180°
Detection range diagonally	8 m
Field of detection	17 m ²
Range adjustment	Mechanical
Recommended installation height	2,5 m
Max. mounting height	3 m
Light measurement	Daylight
Level of brightness	3 - 2000 lx

DATA SHEET


AFL BASIC LED 50 W 4 K WH

Order description	Item number	GTIN
AFL BASIC LED 50W 4000K	EL10810763	4015120810763

Accessories

Product designation	Item number	GTIN
Wall Arm 700 WH	EL10810527	4015120810527
Ground Spike WH	EL10810541	4015120810541

Scale drawing



Energy Conservation Solutions Pty Ltd

Exclusive Distributor for **ESYLUX** in Australia Locations:

VIC/TAS, NSW, QLD, ACT, SA/NT & WA

Phone: **1300 306 136**

For contact details visit: www.ecs.net.au