

DATA SHEET

OFL BASIC LED 10 W 3 K WH

Order description

OFL BASIC LED 10W 3000K

Item number

EL10810787

GTIN

4015120810787



Product description

- LED floodlight with compact aluminium housing for unobtrusive installation, white
- 10 W light output with 3000 K light colour (white)
- Excellent efficiency of approx. 100 lm/W

Technical data

GENERAL

Conformity	CE, RoHS, WEEE
warranty	3-year

MOUNTING

Installation type	Surface mounting
Installation position	Wall

HOUSING

Dimensions	length 160 mm x width 142 mm x Height/Depth 28 mm
Weight	0,45 kg
Housing material	Aluminium and UV-stabilised plastic
Protection type	IP 65
Permissible ambient temperature	-25 °C...+40 °C
Colour	white
Terminal	1.5 mm ²
Glow wire test in accordance with IEC 60695-2-10	650 °C - 30 s

ELECTRICAL VERSION

Protection class	I
Nominal voltage	220 - 240 V / 50 - 60 Hz

LIGHT

Diffusor	transparent
Light emission	Direct
Beam angle	120 °
Unified Glare Rating	<30
Flicker factor	<30%
Rated output	10,0 W
Luminous Flux (light)	1000 lm
Luminous efficacy	100 lm/W
LED service life	L80B50 = 50.000 h
Colour temperature	3000 K
Colour rendering index Ra	>80
Color Quality Scale	>80
Photobiological safety	Risk group 0
Energy efficiency class	A++ to A

DATA SHEET


OFL BASIC LED 10 W 3 K WH

Order description	Item number	GTIN
OFL BASIC LED 10W 3000K	EL10810787	4015120810787

Accessories

Product designation	Item number	GTIN
Wall Arm 700 WH	EL10810527	4015120810527
Ground Spike WH	EL10810541	4015120810541

Scale drawing



Energy Conservation Solutions Pty Ltd

Exclusive Distributor for ESYLUX in Australia Locations:

VIC/TAS, NSW, QLD, ACT, SA/NT & WA

Phone: **1300 306 136**

For contact details visit: www.ecs.net.au