



## **DATA SHEET**

## AFL BASIC LED 30 W 3 K WH

Order description

Item number

GTIN

AFL BASIC LED 30W 3000 K

EL10810848

4015120810848















### **Product description**

Diffusor

- LED floodlight with compact aluminium housing for unobtrusive installation, white
- 30 W light output with 3000 K light colour (white)
- Excellent efficiency of approx. 100 lm/W

### Technical data

| GENERAL  |   |  |
|--|---|--|
| Conformity                                       | CE, RoHS, WEEE  |  |
| warranty   | 3-year  |  |
| MOUNTING   |   |  |
| Installation type                                | Surface mounting                                      |  |
| Installation position                            | Wall  |  |
| HOUSING  |   |  |
| Dimensions                                       | length 215 mm x width 205 mm x Height/<br>Depth 60 mm |  |
| Weight   | 0,93 kg   |  |
| Housing material                                 | Aluminium and UV-stabilised plastic                   |  |
| Protection type                                  | IP 65   |  |
| Permissible ambient temperature                  | -25 °C+40 °C  |  |
| Colour   | white   |  |
| Terminal   | 1.5 mm²   |  |
| Glow wire test in accordance with IEC 60695-2-10 | 650 °C - 30 s   |  |
| ELECTRICAL VERSION                               |   |  |
| Protection class                                 | 1   |  |
|  | 220 - 240 V / 50 - 60 Hz                              |  |

| Light emission                  | Direct   |
|---------------------------------|--|
| Beam angle                      | 120 °  |
| Unified Glare Rating            | <30  |
| Flicker factor                  | <30%   |
| Rated output                    | 30,0 W   |
| Luminous Flux (light)           | 3000 lm  |
| Luminous efficacy               | 100 lm/W   |
| LED service life                | L80B50 = 50.000 h                                  |
| Colour temperature              | 3000 K   |
| Colour rendering index Ra       | >80  |
| Color Quality Scale             | >80  |
| Photobiological safety          | Risk group 0                                       |
| Energy efficiency class         | A++ to A   |
| SENSORS                         |  |
| Detection angle                 | 120° horizontally and vertically rotatable +/-180° |
| Detection range diagonally      | 8 m  |
| Field of detection              | 17 m²  |
| Range adjustment                | Mechanical   |
| Recommended installation height | 2,5 m  |
| Max. mounting height            | 3 m  |
| Light measurement               | Daylight   |
| Level of brightness             | 3 - 2000 lx  |
|                                 |  |

transparent





# **DATA SHEET**

## AFL BASIC LED 30 W 3 K WH


Order description Item number GTIN

AFL BASIC LED 30W 3000 K EL10810848 4015120810848

### **Accessories**

| Product designation | Item number | GTIN          |
|---------------------|-------------|---------------|
| Wall Arm 700 WH     | EL10810527  | 4015120810527 |
| Ground Spike WH     | EL10810541  | 4015120810541 |

### Scale drawing



### **Energy Conservation Solutions Pty Ltd**

Exclusive Distributor for **ESYLUX** in Australia Locations: VIC/TAS, NSW, QLD, ACT, SA/NT & WA
Phone: **1300 306 136** 

For contact details visit: www.ecs.net.au