

DATA SHEET

ALVA 360° 700 / 100 7W 3K WHITE CLEAR ON/OFF

Order description	Item number	GTIN
BL-ALV 65 006 830 WHT	EL10821127	4015120821127



Product description

- LED bollard made from high-grade aluminium
- Dirt-repellent thanks to powder coating with lotus effect
- Integrated ballast (on/off), installation without further accessories
- High-quality housing, die-cast aluminium, powder coated white, similar to RAL 9016
- Colour temperature 3000 K

Technical data

GENERAL	
Conformity	CE, RoHS, WEEE
warranty	5-year
MOUNTING	
Installation type	Free standing
Installation position	Floor
HOUSING	
Dimensions	Height/Depth 700 mm, Ø 100 mm
Weight	3250 g
Housing material	powder-coated aluminium
Protection type	IP 54
Permissible ambient temperature	-25 °C...+40 °C
Relative humidity	5 - 95 %, non-condensing
Colour	white, similar to RAL 9016
Terminal	2,5 mm ² / 1,5 mm ²

ELECTRICAL VERSION

Protection class	I
Nominal voltage	110 - 240 V / 50 - 60 Hz

LIGHT


Diffusor	transparent
Light emission	Direct
Beam angle	160 °
Flicker factor	< 3%
Rated output	7,0 W
Luminous Flux (light)	530 lm
Luminous efficacy	75 lm/W
LED service life	L80B10 = 50.000 h
Colour temperature	3000 K
Colour rendering index Ra	> 80
Color Quality Scale	>80
Photobiological safety	Risk group 0
Energy efficiency class	A++ to A

DATA SHEET

ALVA 360° 700 / 100 7W 3K WHITE CLEAR ON/OFF

Order description	Item number	GTIN
BL-ALV 65 006 830 WHT	EL10821127	4015120821127

Scale drawing



Energy Conservation Solutions Pty Ltd

Exclusive Distributor for ESYLUX in Australia Locations:

VIC/TAS, NSW, QLD, ACT, SA/NT & WA

Phone: 1300 306 136

For contact details visit: www.ecs.net.au