

DATA SHEET

ALVA 2x13° 10W 4K AN On/Off

Order description

UDL-ALV 012 840 AN

Item number

EL10830020

GTIN

4015120830020

IP 65	230 V ~		IK 09		ON/OFF	CRI >80	LED 4000 K
-------	---------	---	-------	---	--------	---------	------------



Product description

- High-quality aluminium LED up/down light
- Dirt-repellent thanks to powder coating with lotus effect
- Beam angle: 2 x 13°

Technical data

GENERAL

Conformity	CE, RoHS, WEEE
warranty	5-year

MOUNTING

Installation type	Surface mounting
Installation position	Wall

HOUSING

Dimensions	length 176 mm x width 100 mm x Height/Depth 160 mm
Weight	1540 g
Housing material	powder-coated aluminium
Protection type	IP 65
Permissible ambient temperature	-25 °C...+40 °C
Impact resistance	IK09
Colour	anthracite grey, similar to RAL 7016
Terminal	2,5 mm ² / 1,5 mm ²
Glow wire test in accordance with IEC 60695-2-10	650 °C - 30 s

ELECTRICAL VERSION

Protection class	I
Nominal voltage	230 - 230 V / 50 Hz

LIGHT

Diffusor	transparent
Light emission	Direct/indirect
Beam angle	13 °
Flicker factor	<10 %
Rated output	10,0 W
Luminous Flux (light)	1050 lm
Luminous efficacy	105 lm/W
LED service life	L80B10 = 50.000 h
Colour temperature	4000 K
Colour rendering index Ra	> 80
Colour tolerance	SDCM <3
Color Quality Scale	80
Energy efficiency class	A++ to A

DATA SHEET

ALVA 2x13° 10W 4K AN On/Off

Order description

UDL-ALV 012 840 AN


Item number

EL10830020

GTIN

4015120830020

Scale drawing



Light distribution

