



## **DATA SHEET**

### PD-FLAT 360i/8 ROUND WHITE

Order description

Item number

GTIN

PD-FLAT 360i/8 RW EP10427930

4015120427930





















### **Product description**

- Design presence detector, approx. range 8 m in Ø
- $\bullet~1$  channel, switching, with zero-cross switching, optimised for LED lights
- Master/slave (parallel wiring)
- Low profile design with plastic design covers: round, white variably interchangeable (alternative: glass, square, black)

### Technical data

GENERAL		
Conformity	CE, RoHS, WEEE	
warranty	5-year	
MOUNTING		
Installation type	Recessed mounting	
Installation position	Ceiling	
Installation dimension	Installation depth 24 mm, Ø 60 mm	
HOUSING		
Dimensions	Height/Depth 6 mm, Ø 94 mm	
Weight	84 g	
Housing material	UV-stabilised polycarbonate	
Protection type	IP 20	
Permissible ambient temperature	0 °C+50 °C	
Relative humidity	5 - 93 %, non-condensing	
Colour	white, similar to RAL 9010	
Terminal	2,5 mm² / 1,5 mm²	
ELECTRICAL VERSION		
Protection class		
Nominal voltage	230 - 230 V / 50 Hz	
SENSORS		
Power consumption	0,3 W	
Detection angle	360°	
Detection range diagonally	8 m	
Detection range head-on	6 m	

Presence detection range	4 m
Field of detection	50 m <sup>2</sup>
Recommended installation height	2,5 m
Max. mounting height	5 m
Light measurement	mixed light
Level of brightness	5 - 2000 lx
Number of light channels	1
Number of switching contacts	0
Slave input	No
Number of parallel switchable detectors	10
Fully automatic	yes
Semi-automatic	yes
Impulse feature	yes
constant lighting control	false
Switching delay from "dark to light" [s]	300 s
Switching delay from "light to dark" [s]	30 s

CONTROL		
Channel 1	Lighting	
Interface	Switching	
Contact	make contact/non-floating	
Switching capacity channel 1	230 V AC 50 Hz, 2300 W/10 A (cos # = 1), 1150 VA/5 A (cos # =0.5)	
In-rush current	78 A / 5 ms	
Switch-off delay channel 1	60 s - 30 min	
Master/slave function	true	
constant lighting control	false	
Manual override	ves	





# **DATA SHEET**

## PD-FLAT 360i/8 ROUND WHITE


Order description Item number GTIN


PD-FLAT 360i/8 RW EP10427930 4015120427930

#### **Accessories**

Product designation	Item number	GTIN
ESY-Pen	EP10425356	4015120425356
Mobil-PDi/MDi-universal	EP10433993	4015120433993
Mobil-PDi/MDi	EM10425509	4015120425509
Basket guard 180/90	EM10425608	4015120425608
Basket guard 165/70	EM10425615	4015120425615
Recessed ceiling mounting kit for FLAT series	EP10426889	4015120426889
Cover FLAT series SQUARE WHITE cover	EP00007248	4015120007248
Cover FLAT series GLASS ROUND WHITE cover	EP00007255	4015120007255
Cover FLAT series GLASS SQUARE WHITE cover	EP00007262	4015120007262
Cover LARGE FLAT series ROUND BLACK	EP10428098	4015120428098
Cover LARGE FLAT series ROUND WHITE	EP10428579	4015120428579

Scale drawing Field of detection






Operating area approx. Ø 4 m
Head-on to detector approx. Ø 6 m

Passage area / diagonally to detector approx. Ø 8 m

### Circuit diagram



Standard operation

## **Energy Conservation Solutions Pty Ltd**

Phone: 1300 306 136
For contact details visit: www.ecs.net.au