



DATA SHEET

PD-FLAT 360i/8 ROUND BLACK

Order description
PD-FLAT 360i/8 RB

Item number

GTIN

EP10427954 4015120427954





















Product description

- Design presence detector, approx. range 8 m in Ø
- $\bullet~1$ channel, switching, with zero-cross switching, optimised for LED lights
- Master/slave (parallel wiring)
- Low profile design with plastic design covers: round, black variably interchangeable (alternative: glass, square, white)

Technical data

GENERAL		
Conformity	CE, RoHS, WEEE	
warranty	5-year	
MOUNTING		
Installation type	Recessed mounting	
Installation position	Ceiling	
Installation dimension	Installation depth 24 mm, Ø 60 mm	
HOUSING		
Dimensions	Height/Depth 6 mm, Ø 94 mm	
Weight	84 g	
Housing material	UV-stabilised polycarbonate	
Protection type	IP 20	
Permissible ambient temperature	0 °C+50 °C	
Relative humidity	5 - 93 %, non-condensing	
Colour	black, similar to RAL 9004	
Terminal	2,5 mm² / 1,5 mm²	
ELECTRICAL VERSION		
Protection class	II	
Nominal voltage	230 - 230 V / 50 Hz	
SENSORS		
Power consumption	0,3 W	
Detection angle	360°	
Detection range diagonally	8 m	
Detection range head-on	6 m	
<u> </u>		

Presence detection range	4 m
Field of detection	50 m ²
Recommended installation height	2,5 m
Max. mounting height	5 m
Light measurement	mixed light
Level of brightness	5 - 2000 lx
Number of light channels	1
Number of switching contacts	0
Slave input	No
Slave input Number of parallel switchable detectors	No 10
·	
Number of parallel switchable detectors	10
Number of parallel switchable detectors Fully automatic	10 yes
Number of parallel switchable detectors Fully automatic Semi-automatic	10 yes yes
Number of parallel switchable detectors Fully automatic Semi-automatic Impulse feature	yes yes yes
Number of parallel switchable detectors Fully automatic Semi-automatic Impulse feature constant lighting control	yes yes yes false

CONTROL	
Channel 1	Lighting
Interface	Switching
Contact	make contact/non-floating
Switching capacity channel 1	230 V AC 50 Hz, 2300 W/10 A (cos # = 1), 1150 VA/5 A (cos # =0.5)
In-rush current	78 A / 5 ms
Switch-off delay channel 1	60 s - 30 min
Master/slave function	true
constant lighting control	false
Manual override	yes





DATA SHEET

PD-FLAT 360i/8 ROUND BLACK


Order description Item number GTIN


PD-FLAT 360i/8 RB EP10427954 4015120427954

Accessories

Product designation	Item number	GTIN
ESY-Pen	EP10425356	4015120425356
Mobil-PDi/MDi-universal	EP10433993	4015120433993
Mobil-PDi/MDi	EM10425509	4015120425509
Basket guard 180/90	EM10425608	4015120425608
Basket guard 165/70	EM10425615	4015120425615
Recessed ceiling mounting kit for FLAT series	EP10426889	4015120426889
Cover FLAT series SQUARE BLACK cover	EP00007286	4015120007286
Cover FLAT series GLASS ROUND BLACK cover	EP00007293	4015120007293
Cover FLAT series GLASS SQUARE BLACK cover	EP00007309	4015120007309
Cover LARGE FLAT series ROUND WHITE	EP10428579	4015120428579
Cover LARGE FLAT series ROUND BLACK	EP10428098	4015120428098


Scale drawing Field of detection





Circuit diagram

Operating area approx. Ø 4 m
 Head-on to detector approx. Ø 6 m
 Passage area / diagonally to detector approx. Ø 8 m



Standard operation

Energy Conservation Solutions Pty Ltd

Exclusive Distributor for **ESYLUX** in Australia Locations: VIC/TAS, NSW, QLD, ACT, SA/NT & WA
Phone: **1300 306 136**

For contact details visit: www.ecs.net.au