ESYLUX•

DATA SHEET

PD-FLAT 360i/8 LARGE ROUND WHITE DALI SET

PD-FLAT-LS 360i/8 RW DALI

Order description

Item number EP10428661



GTIN





Energy Conservation Solutions 'our promise, you'll save'

Product description

- DALI design presence detector with excellent detection capabilities, at least 8 m in diameter
- Low profile design with plastic design covers (Ø 104 mm): round, white variably interchangeable (alternative: square, glass, black)
- Set: DALI bus power supply 200 mA included in delivery

Technical data

Conformity	CE, RoHS, WEEE	
warranty	5-year	
MOUNTING		
Installation type	Recessed mounting	
Installation position	Ceiling	
nstallation dimension	Installation depth 24 mm, Ø 68 mn	
IOUSING		
Dimensions	Height/Depth 6 mm, Ø 104 mm	
Neight	83 g	
lousing material	UV-stabilised polycarbonate	
Protection type	IP 20	
ermissible ambient temperature	0 °C+50 °C	
Relative humidity	5 - 93 %, non-condensing	
Colour	white, similar to RAL 9010	
Ferminal	2,5 mm² / 1,5 mm²	
ELECTRICAL VERSION		
Protection class		
Nominal voltage	230 - 230 V / 50 - 60 Hz	
SENSORS		
ower consumption	0,3 W	
Power consumption	12 mA	
Detection angle	360°	
etection range diagonally	8 m	

Detection range head-on	6 m
Presence detection range	4 m
Field of detection	50 m ²
Recommended installation height	3 m
Max. mounting height	5 m
Light measurement	mixed light
Level of brightness	3 - 1000 lx
Number of light channels	1
Number of switching contacts	0
Slave input	yes, via DALI
Fully automatic	yes
Semi-automatic	yes
constant lighting control	true
Switching delay from "dark to light" [s]	300 s
Switching delay from "light to dark" [s]	30 s
CONTROL	
Channel 1	Lighting
Interface	Switching/Dimming
Contact	Bus system
Switch-off delay channel 1	60 s - 240 min
Orientation light	10 % to 50 % luminous efficiency
Switch-off delay time, orientation light	disabled/approx. 1 minute $-$ 240 minutes
Orientation light	10 % to 50 % luminous efficiency
Switch-off delay time, orientation light	disabled/approx. 1 minute – 240 minutes
Bus voltage	9.5–22.5 V DC
Master/slave function	true
constant lighting control	true

ESYLUX•

DATA SHEET

PD-FLAT 360i/8 LARGE ROUND WHITE DALI SET

Order description	Item number	GTIN
PD-FLAT-LS 360i/8 RW DALI	EP10428661	4015120428661

Manual override

yes, via IR

DALI output 1


DALI bus / Broadcast

Energy Conservation Solutions 'our promise, you'll save'


Accessories

Product designation	Item number	GTIN
ESY-Pen	EP10425356	4015120425356
Mobil-PDi/MDi-universal	EP10433993	4015120433993
Mobil-PDi/MDi	EM10425509	4015120425509
Basket guard 180/90	EM10425608	4015120425608
Basket guard 165/70	EM10425615	4015120425615
Recessed ceiling mounting kit for FLAT series	EP10426889	4015120426889
Surface-mounted box-C IP 20	EP10425370	4015120425370
Cover FLAT series ROUND BLACK cover	EP00007279	4015120007279
Cover FLAT series GLASS ROUND WHITE cover	EP00007255	4015120007255
Cover FLAT series GLASS ROUND BLACK cover	EP00007293	4015120007293
Cover LARGE FLAT series ROUND BLACK	EP10428098	4015120428098
Cover LARGE FLAT series ROUND WHITE	EP10428579	4015120428579

Scale drawing



Field of detection



Operating area approx. Ø 4 m
Head-on to detector approx. Ø 6 m

Passage area / diagonally to detector approx. Ø 8 m

Energy Conservation Solutions Pty Ltd

Exclusive Distributor for ESYLUX in Australia Locations: VIC/TAS, NSW, QLD, ACT, SA/NT & WA Phone: 1300 306 136 For contact details visit: www.ecs.net.au