

DATA SHEET

NOVA 600 30W 4000K MILKY ON/OFF

Order description	Item number	GTIN
PNLNOV10030840WHO0000000	EQ10113406	4015120113406



Product description

- LED light with opal cover (diffuser)
- Can be used as a panel light for ceiling systems with concealed or visible mounting rails for system dimensions 600 x 600 mm (please note any special features and restrictions of the ceiling system manufacturer)
- Excellent light quality, suitable for screen-based work places in accordance with EN 12464-1
- LED service life 50,000 h LM80 B10
- Integrated ballast (on/off), installation without further accessories

Technical data

GENERAL	
Conformity	CE, RoHS, WEEE
warranty	5-year
MOUNTING	
Installation type	Recessed mounting
Mounting location	Ceiling
Installation dimension	Installation length 600 mm x Installation width 600 mm x Installation depth 60 mm
HOUSING	
Dimensions	Length 593 mm x Width 593 mm x Height/Depth 57,6 mm
Weight	5000 g
Material	Varnished steel
Surface finish	frosted
Protection type	IP 20
Permissible ambient temperature	0 °C...+40 °C
Colour	white, similar to RAL 9003
Terminal	2,5 mm ² / 1,5 mm ²
Glow wire test in accordance with IEC 60695-2-10	650 °C - 30 s

ELECTRICAL VERSION

Protection class	I
Nominal voltage	230 - 230 V / 50 Hz
Stand-by consumption	0 W

LIGHT

Diffusor	micro-prismatic / opal
Light emission	direkt
Beam angle	110 °
Unified Glare Rating	≤ 19
Flicker factor	<3 %
Rated output	32 W
Luminous Flux (light)	3330 lm
Luminous efficacy	105 lm/W
LED service life	L70B50 = 100.000 h, L80B50 = 65.000 h, L90B50 = 30.000 h, L80B10 = 50.000 h
Colour temperature	4000 K
Colour rendering index Ra	> 80
Colour tolerance	SDCM <3
Color Quality Scale	CQS > 85
Photobiological safety	Risk group 0
Energy efficiency class	A++ to A

DATA SHEET


NOVA 600 30W 4000K MILKY ON/OFF

Order description	Item number	GTIN
PNLNOV10030840WH00000000	EQ10113406	4015120113406


Accessories

Product designation	Item number	GTIN
PNL 600 UMF SM WH	EQ10113031	4015120113031
PNL drop protection	EQ10121616	4015120121616

Scale drawing



Light distribution



Energy Conservation Solutions Pty Ltd

Exclusive Distributor for ESYLUX in Australia Locations:

VIC/TAS, NSW, QLD, ACT, SA/NT & WA

Phone: **1300 306 136**

For contact details visit: www.ecs.net.au